



Light angle brackets are used in a large number of DIY applications and are commonly used for reinforcing furniture assemblies.

## FEATURES



## Material

- Steel S235JR according to NF EN 10025, electro-galvanized finish.

## Benefits

Versatile connection.



## APPLICATIONS

### Header member


- **Supporting member:** wood, etc.

### For Use With

- Solid wood.
- Panels.
- PVC, etc.

TECHNICAL DATA

Dimensions



References	Dimensions				Fixing Holes	
	A	B	C	Mtl	Leg B	Leg C
EC30/2C50	15	30	30	2	2 Ø 4,5	2 Ø 4,5
EC40/2C50	15	40	40	2	2 Ø 4,5	2 Ø 4,5
EC50/2C50	15	50	50	2	2 Ø 4,5	2 Ø 4,5
EC80/2.5C50	18	80	80	2	2 Ø 5,0	2 Ø 5,0
EC90/3C50	18	90	90	2	2 Ø 5,0	2 Ø 5,0

## INSTALLATION

### Fixing

#### **Countersunk holes:**


- Type 30 to 80 dia. 4.2 mm.
- Type 90 to 140 dia. 5.5 mm.

#### **On wood:**

- CNA annular ring-shank nails dia. 3.1 x 35 mm and dia. 4.0 x 35 mm.
- SD8 screws dia. 4.0 x 32 mm.

### Installation

1. Approcher l'élément à fixer du support,
1. Pointer l'élément. Celui-ci peut aussi être vissé à l'aide de vis adaptées,
2. L'équerre est aussi pointée ou vissée sur celui-ci.



Corner  
reinforcement.