



The DW-C plasterboard screw has been designed to drilling quickly and neatly into plasterboard and timber, including OSB.



[UK-DoP-h10/0013](#)

FEATURES

Material

- Phosphate finish.

Benefits

- Bugle head.
- Tapered point for improved penetration - even without pre-drilling.
- CE marked: EM14566.



BIT2PE



APPLICATIONS

Header member

- Drywall to wood.

For Use With

- Plasterboard to timber.

TECHNICAL DATA

Dimensions and characteristics values

References	Head diameter [mm]	Ø tête [mm]	Length of the screw [mm]	Nbr vis/bande	Nbr vis/carton	Outils compatibles	Vitesse de rotation [tr/min]
DWC3525PE	8.2	3.5	25	30	2500	QDPRO51 / QD76	2500
DWC3535PE	8.2	3.5	35	30	2500	QDPRO51 / QD77	2500
DWC3540PE	8.2	3.5	40	30	2500	QDPRO51 / QD78	2500
DWC3545PE	8.2	3.5	45	30	2000	QDPRO51 / QD79	2500
DWC3550PE	8.2	3.5	50	30	2000	QD76	2500
DWC3925PE	8.2	3.9	25	30	2500	QDPRO51E / QD76KE	2500 - 6000
DWC3930PE	8.2	3.9	30	30	2500	QDPRO51E / QD76KE	2500 - 6000
DWC3935PE	8.2	3.9	35	30	2500	QDPRO51E / QD76KE	2500 - 6000
DWC3940PE	8.2	3.9	40	30	2500	QDPRO51E / QD76KE	2500 - 6000
DWC3945PE	8.2	3.9	45	30	2000	QDPRO51E / QD76KE	2500 - 6000
DWC3955PE	8.2	3.9	55	30	2000	QD76KE	2500 - 4500
DWC3965PE	8.2	3.9	65	30	1500	QD76KE	2500 - 4500

