



The DWF plasterboard screw has been designed to drilling quickly and neatly into plasterboard when fixing to steel of thickness 0.6mm to 0.9mm.



[UK-DoP-h10/0011](#)

FEATURES

Material

- Phosphate Finish.

Benefits

- Bugle head.
- Tapered point for improved penetration - even without pre-drilling.
- CE marked: EM14566.



BIT2PE



APPLICATIONS

Header member

- Drywall to steel (steel thickness 0.6 to 1.2 mm).

For Use With

- Fixing drywall panels to steel.

TECHNICAL DATA

Dimensions and characteristics values

References	Head diameter [mm]	Ø tête [mm]	Longueur tête [mm]	Nbr vis/ bande	Nbr vis/ carton	Outils compatibles	Vitesse de rotation [tr/min]	Vitesse rotation max - DE [U/Min.]	Outils compatibles - DE
DWF3525PE	8.2	3.5	25	30	2500	QDPRO51 / QD76	de 2500 à 6000	2500 - 6000	QDPRO51 / QD76
DWF3535PE	8.2	3.5	35	30	2500	QDPRO51 / QD77	de 2500 à 6000	2500 - 6000	QDPRO51 / QD77
DWF3540PE	8.2	3.5	40	30	2500	QDPRO51 / QD78	de 2500 à 6000	2500 - 6000	QDPRO51 / QD78
DWF3545PE	8.2	3.5	45	30	2000	QDPRO51 / QD79	de 2500 à 6000	2500 - 6000	QDPRO51 / QD79
DWF3925PE	8.2	3.9	25	30	2500	QDPRO51E / QD76KE	2500 - 6000	2500 - 6000	QDPRO51E / QD76KE
DWF3930PE	8.2	3.9	30	30	2500	QDPRO51E / QD76KE	2500 - 6000	2500 - 6000	QDPRO51E / QD76KE
DWF3935PE	8.2	3.9	35	30	2500	QDPRO51E / QD76KE	2500 - 6000	2500 - 6000	QDPRO51E / QD76KE
DWF3940PE	8.2	3.9	40	30	2500	QDPRO51E / QD76KE	2500 - 6000	2500 - 6000	QDPRO51E / QD76KE
DWF3945PE	8.2	3.9	45	30	2000		2500 - 6000	2500 - 6000	

