



Light reinforced angle brackets are used to assemble small structural joinery for internal and external applications.

## FEATURES





### Material

- Pre-galvanised mild steel.

### Benefits

- Multiple applications.



## APPLICATIONS

### Header member



- **Supporting member:** solid wood, composite lumber, glued-laminated wood, triangular trusses, profiles, etc.
- **Supported member:** wood, concrete, steel, etc.

### For Use With

- Interior fittings.
- Furniture.
- Small frames, etc.

TECHNICAL DATA

Dimensions and drill holes



References	Dimensions [mm]				Holes [mm]					
	A	B	C	Thickness	Leg B			Leg C		
					Ø5	Ø11	Oblong	Ø5	Ø11	Oblong
EA444/2C50	40	40	40	2	3	--	--	3	--	--
EA554/2C50	40	50	50	2	4	1	--	4	1	--
EA664/2C50	40	60	60	2	6	--	10x30	4	--	10x20
EA756/2C50	60	70	50	2	6	--	10x42	4	--	12x20

## INSTALLATION

### Fixing

#### **On wood:**

- 3.75 x 30mm square twist nail.
- CNA annular ring-shank nails 4.0 mm.
- CSA screw 5.0 mm.

#### **On concrete:**


- HIPC 6-40/10 drive anchors or HIPC 8-60/20.

#### **On metal:**


- Bolts.
- HR bolts.
- Rivets, etc.

### Installation

Use specified fasteners.



Wood to wood  
connection.



Timber to  
masonry  
connection