Technical data sheet

ECP Light Duty Flat L Bracket

Light angle brackets are used in a large number of DIY applications and are commonly used for reinforcing furniture assemblies.

Features

Material

• Steel S235JR according to NF EN 10025, electrogalvanized finish.

Benefits

- Large range for multi use.
- Suitable for us on timber and concrete.

Applications

Header member

• Supporting member: wood, etc.

For Use With

- Solid wood.
- Panels.
- PVC, etc.









Timber connection


SIMPSON Strong-Tie

ECP Light Duty Flat L Bracket

Technical Data

Product Dimensions

					Timber connection						
References	Product Dimensions [mm]				Joist			Holes flange B			
	Α	В	C	t	Ø3.6	Ø3.8	Ø4.5	Ø3.6	Ø3.8	Ø4.5	
ECP40/1.2	40	40	10	1.2	-	2	-	-	2	-	
ECP60/1.5	60	60	16	1.5	-	-	2	-	-	2	
ECP80/2	80	80	16	2	-	-	2	-	-	2	
ECP100/2	100	100	16	2	-	-	2	-	-	2	



SIMPSON Strong-Tie

ECP

Light Duty Flat L Bracket



Installation

Fixing

Countersunk holes:

- Type 30 to 80 dia. 4.2 mm.
- Type 90 to 140 dia. 5.5 mm.

On wood:

- CNA annular ring-shank nails dia. 3.1 x 35 mm and dia. 4.0 x 35 mm.
- SD8 screws dia. 4.0 x 32 mm.

Installation

- 1. Place the elements together
- 2. Mark out positionsif required
- 3. Fix the elements with nail or screws



Winchester Road Cardinal Point Tamworth Staffordshire B78 ЗНG tel: +44 1827 255600 fax: +44 1827 255616 Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

ECP Light Duty Flat L Bracket





www.strongtie.co.uk

2023-02-15