



EFIXR angle brackets are intended for all assemblies for the design and installation of interior and exterior joinery. EFIXR stiffener improves rigidity particularly for large models.

FEATURES





Material

- Galvanized steel S250GD + Z275 according to NF EN 10346.

Benefits

- The 2 obround holes make adjustments easier.



APPLICATIONS

Header member


- Supporting member type:** wood, concrete, metal, PVC.
- Supported member type:** wood, concrete, metal, PVC.

For Use With

- Frames.
- Storage cabinets.

TECHNICAL DATA

Dimensions and drill holes



| References | Dimensions | | | | Holes | | | |
|-------------|------------|----|----|-----------|----------|--------|----------|--------|
| | A | B | C | Thickness | Leg A | | Leg B | |
| | | | | | Ø5 Holes | Slot | Ø5 Holes | Slot |
| EFIXR553C50 | 50 | 55 | 30 | 2 | 4 | 6,5x30 | 4 | 8,5x30 |
| EFIXR753C50 | 70 | 55 | 30 | 2 | 5 | 6,5x50 | 4 | 8,5x30 |

INSTALLATION

Fixing

Nail holes dia. 5 mm and obround holes width 8.5 and 6.5 mm.

On wood:

- CNA annular ring-shank nails 4.0 mm.
- Bolts.
- LAG screws.
- CSA screws dia. 5.0 mm.

On concrete:


- HIPC 8-60/20 drive anchors.

On metal:

- Bolts.
- Self-drilling screws.

Installation

1. Approcher l'élément à fixer du support,
1. Pointer l'élément. Celui-ci peut aussi être vissé à l'aide de vis adaptées,
2. Si le support est en bois, l'équerre est aussi pointée ou vissée sur celui-ci,
2. Si le support est en béton, fixer l'équerre en respectant les préconisations de pose de l'ancrage choisi.



Wood to wood connection.