



Fuga Fresca

Polymeric paint to refresh the colour of the cementitious grout joints between tiles



WHERE TO USE

Fuga Fresca is a ready-to-use paint for internal areas which is quickly and easily applied to rejuvenate, refresh and modify the colour of cementitious grout joints between tiles.

Some application examples

Fuga Fresca is used to eliminate irregularities in the colour of grout-joints caused, for example, by incorrect application of the mortar, or to eliminate unsightly stains caused during use.

TECHNICAL CHARACTERISTICS

Fuga Fresca is a water-based polymeric, acrylic resin-based paint which, thanks to its special characteristics and excellent covering qualities, allows joints with a uniform colour to be produced with lower water absorption that are easy to clean.

RECOMMENDATIONS

- Do not use for external applications or on surfaces subjected to continuous immersion (swimming pools, basins, etc.).
- If the product is used on terracotta floors or on stone material with a porous, absorbent surface, it must only be applied on the joints to avoid staining the tiles.

- Apply the product on cementitious joints which have been cured for at least 48 hours.
- Do not use on epoxy grouts or on expansion joints sealed with silicone or polyurethane-based products.
- Do not use **Fuga Fresca** to consolidate friable grout or those with poor mechanical strength due to inadequate hydration.
- If the colour difference between the original colour and the new colour is too great, it may be necessary to apply more than one coat.

APPLICATION PROCEDURE

Dosing canister

Shake the canister well before use. Unscrew the cap and apply the product by pressing the sponge applicator lightly on the surface of the joints, which must be clean and free of loose parts, mould and calcium deposits. Wait a few minutes until the product applied on the joints is dry. Remove any traces of the product from the edges of the tiles using a damp sponge. After use, thoroughly clean the sponge applicator on the canister.



Fuga Fresca



Floor in terracotta treated with Fuga Fresca

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	thick liquid
Colours:	available in 40 colours
Density (g/cm ³):	1.37
pH:	8
Dry solids content (%):	58
Brookfield viscosity (Pa·s):	10.6 (# 6 - 10 rpm)
Covering capacity (contrast ratio):	96.93
Dirt pick-up (UNI 10792):	ΔE* 0.27
Abrasion resistance (DIN 53778):	> 10,000 cycles
Weatherometer resistance (ASTM G155), cycle 1:	ΔE* 0.04
Application temperature range:	from +5°C to +35°C
Ready for foot traffic:	2 hours
Waiting time before cleaning the tiling with water:	24 hours

Drum

The product is ready-for-use. Mix the product in the drum thoroughly before use. Using a brush, spread the product on the surface of the joints, which must be clean and free of loose parts, mould and calcium deposits. Wait a few minutes until the product applied on the joints is dry. Remove any traces of the product from the edges of the tiles using a damp sponge.

COLOURS AVAILABLE

Available in 40 colours of the range.

CONSUMPTION

Dependant on the size of the tiles and joints.

PACKAGING

1 kg drums and 160 g dosage canisters.

STORAGE

24 months in its original, sealed container stored under normal conditions. Protect from frost.


SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term

	100 WHITE	103 MOON WHITE	111 SILVER GREY	123 ANCIENT WHITE	112 MEDIUM GREY	113 CEMENT GREY	114 ANTHRACITE	127 ARCTIC GREY	110 MANHATTAN 2000	187 LINEN	176 GREEN-GREY	174 TORNADO	125 CASTLE GREY	119 LONDON GREY	163 LIGHT LILAC	168 CERULEAN	167 AVO	169 STEEL BLUE	172 SPACE BLUE	177 SAGE	130 JASMINE	131 VANILLA	137 CARIBBEAN	132 BEIGE 2000	138 ALMOND	141 CARAMEL	142 BROWN	189 SPELT	133 SAND	134 SILK	188 BISCUIT	135 GOLDEN DUST	152 BROWN	144 CHOCOLATE	149 VOLCANO SAND	145 TERRA DI SIENA	143 TERRACOTTA	136 MUD	120 BLACK	150 YELLOW										
Fuga Fresca	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

N.B.: Due to the printing processes involved, the colours should be taken as merely indicative of the shades of the actual product

practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements

per the TDS in force at the time of the MAPEI product installation. The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com



Fuga Fresca



BUILDING THE FUTURE

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

2803-9-2021 (GB)