

EC76 - Eco Hi-Vis Vest (10 Pack)

Collection: Vest-Port

Range: High Visibility

Inner Pack: 10

Outer Carton: 10

Product information

This version is a sustainable option of our best selling basic vest, using 100% Recycled Polyester. It has a classic reflective tape configuration that will ensure you are seen.

Vest-Port

The Vest-Port™ extensive range of vests covers the varied demands of the work environment from core styles to the revolutionary "Executive" design, which is now available in both summer and winter weights.

High Visibility

Our extensive range of High-Visibility clothing meets stringent requirements in both design and construction, to ensure compliance with the latest EN ISO 20471 & ANSI standards. Innovative and technical, our High Visibility range is ideal for those who will not compromise on style, comfort, protection and performance.

Standards

EN ISO 20471 Class 2
RIS 3279 TOM Issue 2 (Orange Only)
ANSI/ISEA 107 TYPE R CLASS 2
ANSI/ISEA 107 TYPE P CLASS 2



Features

- Lightweight and comfortable
- Made using recycled polyester
- Reflective tape for increased visibility
- Hook and loop closure for easy access
- Generous fit for wearer comfort
- Complies with RIS 3279-TOM for rail industry (orange only)
- Available in sizes up to 5XL
- Certified to EN ISO 20471 after 50x washes
- CE certified
- UKCA marked

EC76 - Eco Hi-Vis Vest (10 Pack)

Commodity Code: 6110309100

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)
 Bracetown Business Park
 D15 YN2P, Ireland
 Cert No: 2777/21758-01/E00-00

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)
 SATRA Technology Park
 NN16 8SD, United Kingdom
 Cert No: AB0321/21826-01/E00-00

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
EC76ORRS/M	Orange	43.0	28.0	52.0	1.5160	0.0626	5036146015672	15036108856852
EC76ORRL/XL	Orange	43.0	28.0	55.0	1.6900	0.0662	5036146015665	15036108856845
EC76ORRXX/3X	Orange	43.0	28.0	55.0	1.7280	0.0662	5036146015689	15036108856869
EC76ORR4X/5X	Orange	43.0	28.0	55.0	2.0820	0.0662	5036146015658	15036108856838