



Wood screw suitable for use with chipboard, OSB and other timber based subfloor materials.



[UK-DoP-h10/0015](#)

## FEATURES

### Material

- Yellow zinc dichromate.

### Benefits

- Serrated, countersunk head.
- Tapered point.
- Coarse thread.



## APPLICATIONS

### Header member

- Wood to wood.

### For Use With

- Subfloor installation.

TECHNICAL DATA

Dimensions and characteristics values

References	Head diameter [mm]	Diameter [mm]	Length of the screw [mm]	Nbr vis/bande	Nbr vis/carton	Outils compatibles	Vitesse rotation max [tr/min]
WSC32E	8.4	4.2	32	30	2500	QDPRO51E / QD 76	2500
WSC38E	8.4	4.2	38	30	2500	QDPRO51E / QDPRO64 / QD 76 / QDPRO76S	2500

Mechanical Properties (EN14592)

References	Characteristic Yield Moment [My,k] [kNm]	Characteristic Withdrawal Parameter [fax,k] [N/mm <sup>2</sup> ]	Characteristic Head Pull Through Parameter [fhead,k] [N/mm <sup>2</sup> ]	Characteristic Tensile Capacity [ftens,k] [kN]	Characteristic Torsional Strength [ftor,k] [Nm]
WSC32E	3.6	11.5	8.1	7	5.1
WSC38E	3.6	11.5	8.1	7	5.1

